

A

Form PTO-1082
ASSISTANT COMMISSIONER FOR PATENTS
Box Application
Washington D.C. 20231

Case Docket No. 6464

Dear Sir:

Transmitted herewith for filing is the patent application of:
Inventor: Willy Michel, Ulrich Haueter and Thomas Frei
For: Sensor System Including a Port Body

Enclosed are: 10 sheets of Specification, 3 sheets of Claims, 1 sheet of Abstract
1 sheet of formal drawings

- ☐ An assignment of the invention to _____.
- ☐ A certified copy of German Priority Application No. 198 22 711.6 filed May 20, 1998.
- ☒ An Information Disclosure Statement including Form PTO-1449 (in duplicate) and ^{Four} ~~two~~ cited references
- ☐ A Verified Statement to establish small entity status under 37 CRR 1.9 and 37 CFR 1.27.


The filing fee has been calculated as shown:

				<input type="checkbox"/> Small Entity		<input checked="" type="checkbox"/> Other than Small Entity	
Basic Filing Fee					\$380.00		\$760.00
Additional Fees:				(rate)		(rate)	
Total Claims	18	No. Extra	0	\$9.00		\$11.00	\$ 0.00
Independent Claims	3	No. Extra	0	\$39.00		\$78.00	\$ 0.00
Multiple dependent claim presented.				\$130.00		\$260.00	
TOTAL							\$760.00

- ☐ Please Charge my Deposit Account No. 04-1420 in the amount of _____. A duplicate copy of this sheet is enclosed.
- ☒ A check in the amount of \$760.00 to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to deposit Account No. 04-1420. A duplicate copy of this sheet is enclosed.
 - ☒ Any additional filing fees required under 37 CFR 1.16.
 - ☐ Any patent application processing fees under 37 CFR 1.17.
- ☐ The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 04-1420. A duplicate copy of this sheet is enclosed.
 - ☐ Any patent application processing fees under 37 CFR 1.17.
 - ☐ The issue fee set in 37 CFR 1.18 at or before the mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b).
 - ☐ Any filing fees under 37 CFR 1.16 for presentation of extra claims.

Date:

May 19, 1999


David E. Bruhn (Reg. No. 36,762)
Dorsey & Whitney LLP
Pillsbury Center South
220 South Sixth Street
Minneapolis, MN 55402
Telephone: 612/340-6317
Attorney for Applicant

Express Mail mailing label number EL303045123US

Date of Deposit May 19, 1999

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington D.C. 20231

Elvina Smith

Name

Elvina Smith

Signature

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

We, Willy Michel of Burgdorf, Switzerland, Ulreich Haueter of Grosshochstetten, Switzerland, and Thomas Frei of Lutzelfluh, Switzerland, all Citizens of Switzerland, have invented certain new and useful improvements in a

Sensor System Including a Port Body

of which the following is a specification.

Title: Sensor System Including a Port Body

RELATED APPLICATIONS

This application claims the priority of German Patent Application No. 198 22 711.6, filed May 20, 1998, which is incorporated herein by reference.

BACKGROUND

The invention relates to a process and a device for accessing and analysing body fluids. More particularly, it relates to an implantable device for providing access to the interior of the body and for providing for detecting the concentration and/or existence of substances in body fluids, wherein the device provides a vehicle for both delivery of substances into the body and for analysing of body fluids. The invention encompasses various embodiments wherein the body fluids may be analysed in situ, or partially or completely extracted or aspirated for analysis.

A number of procedures exist in medicine for detecting the concentration and/or existence of substances in body fluids. When testing for blood sugar concentration, for instance, there is the option on the one hand of piercing the patient's skin, such as on a finger, for testing the blood sugar content of blood drawn in this manner. Virtually any intercellular fluid may be examined in many different ways and for different characteristics using a selected "test strip" after such a fluid has been obtained. Another piercing procedure involves piercing the skin with needles for introducing and/or retrieving a sensor at a test point in the body.

However, a severe disadvantage or drawback of such invasive techniques is that they are generally unpleasant experiences to the patient. Another related drawback is that a piercing may be required for each desired test, and such piercings may be frequent and repeated. In addition,

needle-type sensors will fail due to being affected and/or rejected by the body after a very short time (approximately half a day).

Non-invasive techniques, for instance detecting said concentration by fluoroscopic methods, have not yet been adequately developed to obtain sufficiently accurate values.

Port bodies, implanted subcutaneously or percutaneously and used for administering drugs through tubular channels, are known from at least U.S. Patent 5,306,255 and EP 0 302 076.

SUMMARY

The present invention provides an implantable device for providing access to the interior of the body and for providing for detecting the concentration and/or existence of substances in body fluids, wherein the device provides a vehicle for both delivery of substances into the body and for analysing of body fluids.

It is an object of the invention to provide a method and a device for detecting the concentration and/or existence of substances in body fluids by which the disadvantages of the devices and methods described above are overcome as far as possible. Another object of the present invention is to help avoid pain and inconvenience for patients.

The invention provides a device and method for analysing body fluids wherein the body fluids are accessed via an access means implanted in the body.

The inventive method for detecting the concentration and/or existence of substances in body fluids attains this object by accessing the interior of the body and any fluids to be analysed by an access means implanted permanently or semi-permanently in the body.

Many patients needing regular medication due to the concentrations of certain substances in their body fluids being too low or too high, are being administered the regular medication

the body cells as such, the cell fluid also seems a suitable place to measure the blood sugar content, due to measuring a central average in this case directly at the place of consumption. Accordingly, port bodies according to the present invention are suitable for the administration of insulin into the abdominal cavity and as access points to body fluid to be analysed.

Although said port bodies are invasive devices, one-time implantation typically will be sufficient, whereby, in a port body in accordance with the present invention, a patient no longer must experience the pain and inconvenience of subsequent repeated access to body fluids for testing purposes.

One embodiment of the process according to the invention is characterized by a test sensor being introduced into the interior of the body through the access means for detecting the concentration and/or existence of substances, with detection being performed at that point. This creates a chance for continuous and intermittent testing, whereby the sensor remains at the test site in the interior of the body and is introduced via a separate tube when using a port body comprising a tubular system.

In another embodiment of the invention, a test sensor remaining in the interior of the body takes body fluid from the interior of the body through the access means, followed by analysis at a point remote from the point of retraction. Body fluid is still analysed, for instance, within the body, preferably at an intermediate point of the tubular system, by means of a sensor and is aspirated for this purpose to a selected point. The benefit of using an intermediate point as a test site is that any deposits, which might arise at the end of the tube, by which access may be effected, will not have any negative influence on the accuracy of tests. Also, the tubular section between the ends, both interior and exterior, protects a test sensor provided at an intermediate

are withdrawn. The microprobe may be either permanently or removably associated with the access means.

Furthermore, the invention refers to the use of an access means to the interior of the body, permanently or semi-permanently implanted in the body, through which the concentration and/or existence of substances in body fluids are detected and/or analysed.

Other objects, features, embodiments and advantages of the device and method of the present invention will become more fully apparent and understood with reference to the following description and appended drawings and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 depicts an implanted port body adapted according to the present invention.

DETAILED DESCRIPTION

The accompanying Figures and this description depict and describe embodiments of the port body and methods of the present invention, and features and components thereof. With regard to means for fastening, mounting, attaching or connecting the components of the present invention to form the device as a whole, unless specifically described otherwise, such means are intended to encompass conventional fasteners such as threaded connectors, snap rings, clamps such as screw clamps and the like, rivets, toggles, pins and the like. Components may also be connected by adhesives, glues, welding, ultrasonic welding, and friction fitting or deformation, if appropriate. Unless specifically otherwise disclosed or taught, materials for making components of the present invention may be selected from appropriate materials such as metal, metallic alloys, natural and manmade fibers, vinyls, plastics and the like, and appropriate manufacturing or production methods including casting, extruding, molding and machining may be used.

Any references to front and back, right and left, top and bottom and upper and lower are intended for convenience of description, not to limit the present invention or its components to any one positional or spacial orientation.

Referring then to Figure 1, a port body 10, an implantable or partially implantable device for operably coupling a conduit or hose outside of a human or animal body to a catheter, hose, conduit or the like inside the body, is shown implanted in the skin 15 of a patient (human, animal, etc.). The port body 10 comprises a shaft section 11 to which an approximately disc-shaped anchoring section 13 is attached, acting as an anchor or attachment for anchoring, attaching and/or stabilizing the port body 10 in (or under) the skin.

The shaft section 11 forms a hollow enclosure containing and/or supporting an elastic self-closing diaphragm 12.

Separate tubes extend generally perpendicularly away from the innermost, lower end of the port body 3, including a feed tube 23 (the full length of which is not shown) and a shorter aspiration tube 21. A feed catheter 24 and an aspiration catheter 22 may be introduced through the diaphragm 12 into each of the tubes 23 and 21, respectively. Although the tubes are shown as extending perpendicularly away from the port body 3, they may extend away therefrom at another angle. Also, in some situations, a port body may have more than two associated tubes, and the tubes 23, 21 may be adapted to contain more than one catheter each.

The tube 23, either the mouth thereof or a point or points along the tube 23, is supplied with a drug, such as insulin, through the feed catheter 24, whilst from a point or points adjacent to or at the end of the tube 21, e.g., at its open mouth, body fluids may be withdrawn through the aspiration catheter 22.

Figure 1 shows fastening sections 14 at the top of the shaft 11, provided for connection of the upper sealing and/or closing caps of the catheters 24 and 22, not shown in the Figure.

The feed tube 23 is preferably of a standard length of 150 or 180 mm, whilst the aspiration tube 21 presumably has an approximate minimum length of 30 mm, preferably 60 to 120 mm, possibly even 180 mm. This arrangement therefore clearly shows that this port body may be used both for the supply of drugs through the feed catheter 24 and for access to body fluids through the aspiration catheter 22. The tubes 23 and 21 preferably extend into the patient's abdominal cavity where cell fluid can be found, which may be provided with a drug or analysed for specific concentrations.

The dashed arrows show selected various test sites for testing the concentration or existence of certain substances. For example, a sensor may be applied to test point 25 where fluid is aspirated from the bottom end of the catheter 22 somewhat upwards, in order to perform a test precisely at this intermediate point 25. As described above, a sensor attached at point 25 would be protected against deposits by the lower section of the tube 21 and/or the catheter 22.

When a test is performed at a point where no major deposits are to be expected, a test sensor may also be attached permanently or removably at a point marked by the dashed arrow 26. The benefit of this detection method lies in the fact that aspiration is no longer required and detection will be feasible directly at a specified test point.

In the two embodiments described, where the test sensor remains permanently in the tube 25 and/or on the end of the tube 26, an electronic test sensor is used, the connecting wires of which may be routed out of the body together with the catheter 22.

CLAIMS

What is claimed is:

1. A method for analysing body fluids, in which a fluid is accessed for analysis via an access means implanted in the body.
2. The method as set forth in claim 1, wherein access is provided via a permanently implanted device for administering medicaments.
3. The method as set forth in claim 1, wherein access is provided via a port body implanted in the skin, including a tube arrangement extending into the interior of the body.
4. The method as set forth in claim 1, wherein a test sensor is inserted into the interior of the body via said access means for detecting the concentration and/or existence of substances.
5. The method as set forth in claim 4, wherein said test sensor remains at a test site in the interior of the body for continuous testing, said test sensor being inserted via said access means.
6. The method as set forth in claim 1, wherein a body fluid is withdrawn from the interior of the body via said access means and analysed at a location remote from the point of withdrawal.
7. The method as set forth in claim 3, wherein a body fluid is analysed by means of a sensor while still in the body, preferably at an intermediate site of said tube arrangement, said body fluid being aspirated towards this site.
8. The method as set forth in claim 1, wherein a body fluid is analysed outside the body.
9. The method as set forth in claim 1, wherein the body fluids contain substances withdrawn by means of a microdialysis probe associated with said access means.

10. A device for detecting the concentration and/or existence of substances in body fluids, said device comprising an access means for accessing the interior of the body, said access means implantable in the body and adapted to allow access to the body fluids.

11. The device as set forth in claim 10, wherein said access means is a permanently implantable device for administering medicaments and comprises a tube arrangement extending into the interior of the body.

12. The device as set forth in claim 10, wherein said access means comprises a port body, implantable in the skin and comprising passages through which a test sensor may be guided into the interior of the body.

13. The device as set forth in claim 12, said port body further comprising a separate tube for the insertion of a test sensor.

14. The device as set forth in claim 10, said access means associated with a microdialysis probe via which substances in the body fluid may be withdrawn.

15. The device as set forth in claim 10, said access means comprising a port body implanted in the skin of a body, and comprising a shaft section to which a generally disc-shaped anchoring section is attached, said shaft section providing a generally hollow enclosure containing an elastic self-closing diaphragm, a feed tube and an aspiration tube extending away from said shaft section and into an interior region of the body, a feed catheter and an aspiration catheter received respectively in said feed tube and said aspiration tube.

16. A method of analysing body fluids comprising the steps of:

providing an port member for accessing the interior of a body, said port member
implanted in the body; and


testing body fluids via said port member.

17. The method according to claim 16, wherein the port member provides for the delivery of substances into the body.

18. The method according to claim 17, wherein said port member provides for one of the partial or complete extraction of body fluids.

ABSTRACT

The invention provides a device and methods for analysing body fluids wherein the device is implanted in the body and provides for both the delivery of substances into the body and for the testing of body fluids.



66790" 6747E60